


SPECIFICATIONS

Features:	Electrical:(Option)	Application
• Constructed of thick extruded aluminum • Aluminum Parabolic louver locked by four clamping springs with tool-less design • Finish in anodized aluminum, other custom color are option • Easy for lamp replacement and maintance • Suitable for T5 T8 configurations • Available in two lamps model • Available in 24 inch to 60 inch • Suspended	• G13 G5 lampholder from BJB,AAG stucchi or others • Terminal block,Quick disconnecter from IDEAL or WAGO • 220-240V electronic ballast from TRIDONIC,PHILIPS,VS,OSRAM • ADVANCE,FULHAM,GE,SYLVANIA,UNIVERSAL ballast etc • Emergency kits or dimmable ballast,occupany sensor • Linear fluoresecent lamp from GE,Philips,Osram etc • CCC,CE,CB,CSA,UL cUL listed	• Office • Libraries • Classrooms • Conference room • Retail applications



DIMENSIONS

Model	Lamp type	Lamps	Length	Width	Height
BL1-Y14x2	F14T5	2x14W	23 7/8	9 2/8	2 4/8
BL1-Y28x2	F28T5,F54T5HO	2x28W/54W	47 4/8	9 2/8	2 4/8
BL1-Y35x2	F35T5,F49T5HO	2x35W/49W	59 2/8	9 2/8	2 4/8
BL1-Y17x2	F17T8	2x17W	25 3/8	9 2/8	2 4/8
BL1-Y32x2	F32T8	2x32W	49 3/8	9 2/8	2 4/8

NOTE: (1)All dimensions are inches, 1inch=25.4mm (2)T8 fluorescent tube US 17W=NON-US 18W,US 32W=NON-US 36W