

SPECIFICATIONS

Features:


- Constructed of die-formed heavy gauge cold rolled steel
- Aluminum Parabolic louver locked by four clamping springs with tool-less design
- Painted with a lighting grade baked matt enamel, having a high reflectance factor for premium
- Easy for lamp replacement and maintance
- Suitable for T5 T8 configurations
- Available in three lamps model
- Available in 24 inch to 60 inch
- Suspended

Electrical:(Option)

- G13 G5 lampholder from BJB,AAG stucchi or others
- Terminal block,Quick disconnecter from IDEAL or WAGO
- 220-240V electronic ballast from TRIDONIC,PHILIPS,VS,OSRAM
- ADVANCE,FULHAM,GE,SYLVANIA,UNIVERSAL ballast etc
- Emergency kits or dimmable ballast,occupany sensor
- Linear fluorescent lamp from GE,Philips,Osram etc
- CCC,CE,CB,CSA,UL cUL listed

Application

- Office
- Libraries
- Classrooms
- Conference room
- Retail applications



DIMENSIONS

Model	Lamp type	Lamps	Length	Width	Height
BL3 -Y14x3	F14T5	3x14W	26 1/8	10 5/8	2 6/8
BL3 -Y28x3	F28T5,F54T5HO	3x28W/54W	50 5/8	10 5/8	2 6/8
BL3 -Y35x3	F35T5,F49T5HO	3x35W/49W	62 3/8	10 5/8	2 6/8
BL3 -Y17x3	F17T8	3x17W	28 4/8	10 5/8	2 6/8
BL3 -Y32x3	F32T8	3x32W	52 4/8	10 5/8	2 6/8
BL3 -Y58x3	F58T8	3x58W	60 3/8	10 5/8	2 6/8

NOTE: (1)All dimensions are inches,1inch=25.4mm (2)T8 fluorescent tube US 17W=NON-US 18W,US 32W=NON-US 36W